

Tekniske data

Fluke AC175 Alligator Clip Set





Nøkkelfunksjoner

- Insulated alligator clips with flexible boots, threaded shaft for secure probe attachment, 7mm jaw opening, and nickel-plated steel contacts
- Provides reliable and secure connections for precise electrical measurements
- Rated CAT II 1000 V, CAT III 1000 V, CAT IV 600 V, 10 A
- see compatible products below

Produktoversikt: Fluke AC175 Alligator Clip Set

Modular clips are used with modular test leads to offer additional flexibility to configure your leads to your individual needs. The insulated alligator clip jaws provide a 7 mm opening with flexible boots.

The Fluke AC175 Threaded Alligator Clip Set comes with a one-year warranty and a cat rating of CAT III 1000 V, CAT IV 600 V, 10 A.

This alligator clip set has slide-on alligator clips (red, black) compatible with multiple Fluke test probes:

Fluke TL71 Premium Test Lead Set

Fluke TL75 Hard Point™ Test Lead Set

Fluke TL175 TwistGuard™ Test Leads

Fluke TP175 TwistGuard™ Test Probes

Spesifikasjoner: Fluke AC175 Alligator Clip Set

Jaw opening	7 mm (0.275 in), jaw contact material: nickel-plated steel
Category Rating	CAT III 1000 V, CAT IV 600 V, 10 A
Operating temperature	-20u00b0C to 55u00b0C (-4u00b0F to 131u00b0F)
Environmental Information	Pollution Degree 2, 2000 m altitude

Modeller



Fluke AC175

AC175 Alligator Clip Set

Optional accessories	Description
TL71 Testledningssett	Comfort grip, silicone insulated. μV measurement recommended.
TL175 TwistGuard™-testledninger	Den patenterte forlengbare spissbeskyttelsen oppfyller de nye elektriske sikkerhetskravene for å redusere eksponering av spissen og samtidig gi den nødvendige allsidigheten som kreves for de fleste målinger.
Fluke TP175 TwistGuard™ Test Probes	The Fluke TP175 TwistGuard® Test Probes have adjustable tip lengths that allow you to work safely in different settings.
TL75 Testledningssett	PVC-insulated, right-angle shrouded 4 mm (0.16 in) banana plugs

Fluke. *Keeping your world up and running.®*

Fluke Norge AS
Postboks 383
1411 Kolbotn
Tlf: 800 18 227
E-mail: cs.no@fluke.com
www.fluke.no

©2024 Fluke Corporation. Med enerett.
Informasjonen kan endres uten varsel. Vi tar
forbehold om trykkfeil.
11/2024

**Endring av dette dokumentet er ikke tillatt uten
skriftlig tillatelse fra Fluke Corporation.**