

Tekniske data

# AC288 Terminal Block Probe with Retractable Probe Tip





## Nøkkelfunksjoner

- Retractable probe tip designed for increased safety, while providing flexibility to reach deep connection points
- Recommended for use with TL224, TL222 or TL221 Test Leads
- 11.5 cm (4.5 in) insulated, flexible shaft
- 1 mm diameter probe tip extends out to 8.4 mm (0.33 in) length
- Retractable probe tip is made with stainless steel
- Safety rated: IEC 61010-031, CAT III 1000 V, CAT IV 600 V
- Operating temperature: -20 °C to 55 °C (-4 °F to 131 °F), 90% RH
- One-year warranty

## Produktoversikt: AC288 Terminal Block Probe with Retractable Probe Tip

Use for safe and secure connections to clamp and screw type terminal blocks.

## Modeller



**AC288**

---

**Fluke.** *Keeping your world up and running.*®

**Fluke Norge AS**  
Postboks 383  
1411 Kolbotn  
Tlf: 800 18 227  
E-mail: [cs.no@fluke.com](mailto:cs.no@fluke.com)  
[www.fluke.no](http://www.fluke.no)

©2024 Fluke Corporation. Med enerett.  
Informasjonen kan endres uten varsel. Vi tar  
forbehold om trykkfeil.  
11/2024

**Endring av dette dokumentet er ikke tillatt uten  
skriftlig tillatelse fra Fluke Corporation.**