

Tekniske data

Fluke TP175 TwistGuard™ Test Probes



Nøkkelfunksjoner

- Patented TwistGuard™ extendable tip shroud ensures electrical safety by reducing tip exposure while preserving versatility for different measurements
- Known for superior quality, ensuring reliable and accurate testing in industrial environments
- Rated CAT II 1000 V, CAT III 1000 V, CAT IV 600 V
- see compatible products below

Produktoversikt: Fluke TP175 TwistGuard™ Test Probes

- Adjustable tip length, allowing increased safety and precision
- Compatible with the TL22x series, TL238 and TL27 test leads
- Conforms to EN61010-031
- CAT II 1000 V, CAT III 1000 V, CAT IV 600, 10 A rating, CSA Listing
- One-year warranty

Spesifikasjoner: Fluke TP175 TwistGuard™ Test Probes

Specifications	
Ratings	CAT II 1000 V, CAT III 1000 V, CAT IV 600 V, 10 A max., Pollution Degree 2
Exposed probe tip length	19 mm to 4 mm (0.75 inch to 0.16 inch)
Environmental ratings	-20u00b0C to 55u00b0C (-4u00b0F to 131u00b0F) ttaltitude: 2000 m (6,562 ft)
TL175 and TL175E also available. TL175E includes removable 4 mm lante tips that thread onto the lead tip. tt ttConforms to EN61010-031	

Modeller



Fluke TP175

TwistGuard™ Test Probes

Fluke. *Keeping your world up and running.®*

Fluke Norge AS
Postboks 383
1411 Kolbotn
Tlf: 800 18 227
E-mail: cs.no@fluke.com
www.fluke.no

©2024 Fluke Corporation. Med enerett.
Informasjonen kan endres uten varsel. Vi tar
forbehold om trykkfeil.
11/2024

**Endring av dette dokumentet er ikke tillatt uten
skriftlig tillatelse fra Fluke Corporation.**